Mini-6S+ Core Alignment

DESCRIPTION

The Smallest and Most Rugged Core Alignment Splicer - Core Alignment Fusion Splicer with 6 motors

900um/250um holder included

Size: 4.8 x 4.88 x 5.4 (in) Weight: 3.06 lbs. (w/o battery)

Fastest Splicing Time

6 sec with single mode fiber 10 sec Heating time * 6 sec with continuous heating mode Comes with 2 Battery Packs Full Touch Screen SOC Compatible and Includes



Product number

Product name

1665500

6S+ Core Alignment AOCAT Fusion splicer BLE Complete package



Melbye Group | Fordonsvägen 17 | SE-553 02 Jönköping | Tlf +46 36 332 07 00 | info@melbye.se | www.melbye.se

Μ Melbye Group - Region Danmark | Fordonsvägen 17 | DK-553 02 Jönköping | Tlf +45 57 60 09 60 | melbye@melbye.as | www.melbye.as

E Melbye Group | Prost Stabels vei 22 | Postboks 160 | NO-2019 Skedsmokorset | Tif +47 63 87 01 50 | ms@melbye.no | www.melbye.no

Melbye Ltd |The Technology Centre Station Road, Framilingham Woodbridge, IP13 9EZ United Kingdom | +44 (0)7903 288561 | te@melbye.se | melbyefibre.com В Y F