




# **ENVIRONMENTAL PRODUCT DECLARATION**


IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

192F Micro Optical fibre cable 200μm Melbye Skandinavia Sverige



## **EPD HUB, EPD number XXXXX**

Published on XXX, last updated on XXX, valid until XXX







# **GENERAL INFORMATION**

## **MANUFACTURER**

Manufacturer	Melbye Skandinavia Sverige
Address	Prost Stabels Vei 22, 2019 Skedsmokorset, Norway
Contact details	kontakt@melbye.no
Website	https://melbye.com/

## **EPD STANDARDS, SCOPE AND VERIFICATION**


Program operator	EPD Hub, hub@epdhub.com
Reference standard	and ISO 14025
PCR	EPD Hub Core PCR Version 1.1, 5 Dec 2023
Sector	Manufactured product
Category of EPD	Third party verified EPD
Parent EPD number	
Scope of the EPD	Cradle to gate with options, A4-A5, and modules C1-C4, D
EPD author	Aditya Dharmendra Nishad
EPD verification	Independent verification of this EPD and data, according to ISO 14025:  ☐ Internal verification ☐ External verification
EPD verifier	#VERIFIER#

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if

they do not comply with EN 15804 and if they are not compared in a building context.

### **PRODUCT**

Product name	192F Micro Optical fibre cable 200μm
Additional labels	See appendix
Product reference	144F Micro optical fibre cable 200μm, 192F Micro optical fibre cable 200μm, 240F Micro optical fibre cable 200μm, 288F Micro optical fibre cable 200μm, 432F Micro optical fibre cable 200μm, 576F Micro optical fibre cable 200μm,
Place of production	Sterlite Technologies Limited, Survey no. 68/1, Madhuban Dam Rd, Rakholi, Silvassa, Dadra and Nagar Haveli and Daman and Diu 396240
Period for data	1st January 2023 - 31st December 2023
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	0 %





### **ENVIRONMENTAL DATA SUMMARY**

Declared unit	1 Unit
Declared unit mass	48 kg
GWP-fossil, A1-A3 (kgCO₂e)	1.12E+03
GWP-total, A1-A3 (kgCO₂e)	1.08E+03
Secondary material, inputs (%)	1.06
Secondary material, outputs (%)	15.2
Total energy use, A1-A3 (kWh)	4330
Net freshwater use, A1-A3 (m³)	14.8

# PRODUCT AND MANUFACTURER

#### **ABOUT THE MANUFACTURER**

Melbye Group is one of Norway's oldest family-owned companies, with a history dating all the way back to 1907. We have a proud tradition of technical innovation and trade, and today, we are a leading provider of forward-thinking products and system solutions for critical infrastructure. We have expertise within transmission and utilities, fiber, ducts and chambers and safety.

We serve customers throughout the Nordic region and the United Kingdom, engage with stakeholders across Europe, and collaborate with around 200 partners and suppliers.

While our headquarters are located just outside Oslo, Norway, we also have offices at multiple locations in Norway, Sweden, and the United Kingdom, as

well as representatives in Finland, India and China. Together, we are more than 120 co-workers who share the company's core values: Innovation, teamwork, and professionalism.

With advanced expertise spread across our core areas and a dedication to long-term operation and future-oriented development, we stand at the forefront of addressing future challenges. We take pride in contributing to the development of critical infrastructure that will shape tomorrow's society.

#### PRODUCT DESCRIPTION

An optical fiber cable, also called a fiber optic cable, is a cable containing one or more thin strands of glass fibers that transmit data signals in the form of light pulses, allowing for high-speed data transmission over long distances due to the principle of total internal reflection, and are immune to electromagnetic interference because they carry light instead of electrical current; essentially acting as a pipe for light signals to travel through.

Composition: Each fiber consists of a central glass core surrounded by a cladding layer, which helps to contain the light within the fiber.

Data transmission: Light pulses are encoded with data at the sending end and decoded at the receiving end.

Benefits: High bandwidth, low signal loss, immunity to electromagnetic interference, suitable for long-distance data transmission.

Applications: Telecommunications, internet, cable television, data centers, medical imaging.

## This EPD covers the products:

144F Micro optical fibre cable 200μm,


192F Micro optical fibre cable 200 $\mu\text{m}$ ,

240F Micro optical fibre cable 200 $\mu$ m,

288F Micro optical fibre cable 200μm,

432F Micro optical fibre cable 200μm,

576F Micro optical fibre cable 200 $\mu$ m,





In the annex to this EPD, a scaling table is provided to reflect the GWP impacts for the range of products produced in the same plant.

Further information can be found at https://melbye.com/.

### PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass %	Material origin
Metals	0	India
Minerals	100	India
Fossil materials		
Bio-based materials		

### **BIOGENIC CARBON CONTENT**

Product's biogenic carbon content at the factory gate


Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	11.16

### **FUNCTIONAL UNIT AND SERVICE LIFE**

Declared unit	1 Unit
Mass per declared unit	48 kg
Functional unit	
Reference service life	25 years

## **SUBSTANCES, REACH - VERY HIGH CONCERN**

The product does not contain any REACH SVHC substances in amounts greater than 0.1% (1000 ppm).





# **PRODUCT LIFE-CYCLE**

### **SYSTEM BOUNDARY**

This EPD covers the life-cycle modules listed in the following table.

Product stage Assembly stage							U	se sta	ge		E	nd of li	ife stag	Beyond the system boundaries							
A1	A2	А3	A4	A5	B1	B2	В3	B4	В5	В6	В7	<b>C1</b>	C2	С3	C4		D				
×	×	×	×	×	MND	MND	MND	MND	MND	MND	MND	×	×	×	×		×				
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling			

Modules not declared = MND. Modules not relevant = MNR

## **MANUFACTURING AND PACKAGING (A1-A3)**

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

### **TRANSPORT AND INSTALLATION (A4-A5)**

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

Cable's end use is in Norway and Sweden, accordingly shipping distance plus distance from port to customer is considered as 50Km as an average distance

### PRODUCT USE AND MAINTENANCE (B1-B7)

This is not in scope of this EPD


Air, soil, and water impacts during the use phase have not been studied.

## PRODUCT END OF LIFE (C1-C4, D)

Installation of product is done manually however we have considered 0.01kwh/kg as standard as energy used in removing the Micro cable (energy consumption during demolition) from the line. As these Micro cable are used in Norway and Sweden transport by lorry (16-32 Metric tons) class Euro 6 and distance as 50 kms is considered, the entire product is incinerated after been used.


D -


For wooden untreated wooden wheel, wood incineration energy and heat benefit is accounted for as per Wood packaging EU scenario.





# **MANUFACTURING PROCESS**





# LIFE-CYCLE ASSESSMENT

### **CUT-OFF CRITERIA**

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

### **ALLOCATION, ESTIMATES AND ASSUMPTIONS**

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	Partly allocated by mass or volume
Packaging material	No allocation
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume


#### **AVERAGES AND VARIABILITY**

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	0 %

This EPD is product and factory specific and does not contain average calculations.

### LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.10.1 and One Click LCA databases as sources of environmental data.






ME I BY E

# **ENVIRONMENTAL IMPACT DATA**

## CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
GWP – total <sup>1)</sup>	kg CO₂e	2.85E+02	7.58E+01	7.21E+02	1.08E+03	4.95E+01	4.78E+01	MND	4.81E-02	5.84E-01	5.51E+01	1.02E+00	-2.49E+01						
GWP – fossil	kg CO₂e	2.83E+02	7.57E+01	7.61E+02	1.12E+03	4.95E+01	6.85E+00	MND	4.81E-02	5.84E-01	5.52E+01	1.02E+00	-1.91E+01						
GWP – biogenic	kg CO₂e	1.02E-01	0.00E+00	-4.09E+01	-4.08E+01	0.00E+00	4.09E+01	MND	0.00E+00	0.00E+00	-9.46E-02	0.00E+00	-5.77E+00						
GWP – LULUC	kg CO₂e	1.85E+00	3.39E-02	7.76E-01	2.65E+00	2.21E-02	8.90E-04	MND	4.92E-06	2.61E-04	2.18E-03	6.25E-05	-4.48E-02						
Ozone depletion pot.	kg CFC-11e	1.58E-04	1.12E-06	4.08E-06	1.63E-04	7.30E-07	1.26E-08	MND	7.36E-10	8.62E-09	6.04E-08	2.47E-09	-2.80E-07						
Acidification potential	mol H⁺e	1.33E+00	2.58E-01	3.42E+00	5.01E+00	1.69E-01	5.42E-03	MND	4.34E-04	1.99E-03	1.55E-02	6.80E-04	-1.09E-01						
EP-freshwater <sup>2)</sup>	kg Pe	1.09E-01	5.90E-03	2.83E+00	2.95E+00	3.85E-03	1.64E-04	MND	1.39E-06	4.55E-05	-1.58E-01	1.01E-05	-1.46E-02						
EP-marine	kg Ne	3.48E-01	8.49E-02	6.27E-01	1.06E+00	5.54E-02	4.30E-03	MND	2.01E-04	6.54E-04	6.00E-03	2.26E-03	-1.73E-02						
EP-terrestrial	mol Ne	2.76E+00	9.23E-01	6.53E+00	1.02E+01	6.03E-01	2.39E-02	MND	2.20E-03	7.12E-03	5.77E-02	2.77E-03	-1.60E-01						
POCP ("smog") <sup>3</sup> )	kg NMVOCe	9.45E-01	3.81E-01	1.89E+00	3.22E+00	2.49E-01	7.35E-03	MND	6.57E-04	2.93E-03	1.78E-02	1.21E-03	-5.22E-02						
ADP-minerals & metals <sup>4</sup> )	kg Sbe	4.49E-03	2.11E-04	7.53E-04	5.45E-03	1.38E-04	2.74E-06	MND	1.72E-08	1.63E-06	1.64E-05	2.15E-07	-3.28E-05						
ADP-fossil resources	MJ	4.30E+03	1.10E+03	9.61E+03	1.50E+04	7.18E+02	1.09E+01	MND	6.29E-01	8.47E+00	2.90E+01	2.12E+00	-3.83E+02						
Water use <sup>5)</sup>	m³e depr.	1.72E+02	5.43E+00	4.57E+02	6.34E+02	3.55E+00	3.53E-01	MND	1.57E-03	4.19E-02	1.60E+00	1.04E-02	-8.95E+00						

<sup>1)</sup> GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.





1 E L 3 Y

## ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF


Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	СЗ	C4	D
Particulate matter	Incidence	1.61E-05	7.58E-06	2.49E-05	4.86E-05	4.95E-06	1.04E-07	MND	1.23E-08	5.85E-08	1.97E-07	1.54E-08	-6.61E-07						
Ionizing radiation <sup>6)</sup>	kBq 11235e	7.19E+00	9.57E-01	4.38E+01	5.20E+01	6.25E-01	2.72E-02	MND	2.79E-04	7.38E-03	7.32E-02	2.11E-03	-9.42E+00						
Ecotoxicity (freshwater)	CTUe	7.75E+02	1.55E+02	2.12E+03	3.05E+03	1.02E+02	4.84E+00	MND	3.46E-02	1.20E+00	5.33E+01	3.17E+00	-4.25E+01						
Human toxicity, cancer	CTUh	3.36E-08	1.25E-08	1.05E-07	1.51E-07	8.16E-09	5.62E-10	MND	4.94E-12	9.64E-11	4.04E-09	5.00E-11	-3.89E-09						
Human tox. non-cancer	CTUh	1.07E-06	7.12E-07	3.23E-06	5.01E-06	4.65E-07	2.43E-08	MND	7.82E-11	5.49E-09	9.30E-08	9.86E-09	-1.66E-07						
SQP <sup>7)</sup>	-	8.20E+02	1.11E+03	1.05E+03	2.98E+03	7.23E+02	8.95E+00	MND	4.41E-02	8.53E+00	1.94E+01	4.96E+00	-9.34E+01						

6) EN 15804+A2 disclaimer for lonizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

### **USE OF NATURAL RESOURCES**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	С3	C4	D
Renew. PER as energy <sup>8)</sup>	MJ	1.65E+02	1.51E+01	1.25E+03	1.43E+03	9.84E+00	-1.84E+02	MND	3.98E-03	1.16E-01	-5.82E+00	3.33E-02	-4.63E+01						
Renew. PER as material	MJ	9.07E+00	0.00E+00	3.76E+02	3.85E+02	0.00E+00	-3.76E+02	MND	0.00E+00	0.00E+00	-9.07E+00	0.00E+00	5.03E+01						
Total use of renew. PER	MJ	1.74E+02	1.51E+01	1.63E+03	1.81E+03	9.84E+00	-5.59E+02	MND	3.98E-03	1.16E-01	-1.49E+01	3.33E-02	3.95E+00						
Non-re. PER as energy	MJ	3.63E+03	1.10E+03	9.43E+03	1.42E+04	7.18E+02	-1.92E+02	MND	6.29E-01	8.47E+00	-1.00E+03	-3.33E+02	-3.83E+02						
Non-re. PER as material	MJ	6.44E+02	0.00E+00	1.64E+02	8.08E+02	0.00E+00	-1.64E+02	MND	0.00E+00	0.00E+00	-6.44E+02	0.00E+00	3.32E+00						
Total use of non-re. PER	MJ	4.28E+03	1.10E+03	9.60E+03	1.50E+04	7.18E+02	-3.55E+02	MND	6.29E-01	8.47E+00	-1.65E+03	-3.33E+02	-3.80E+02						
Secondary materials	kg	5.08E-01	4.68E-01	1.08E+00	2.06E+00	3.06E-01	1.29E-02	MND	2.61E-04	3.61E-03	8.41E-02	7.69E-04	-4.11E-02						
Renew. secondary fuels	MJ	3.81E-01	5.94E-03	6.21E-03	3.93E-01	3.88E-03	1.07E-04	MND	6.83E-07	4.58E-05	4.16E-04	1.44E-05	-1.85E-04						
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						
Use of net fresh water	m³	4.06E+00	1.63E-01	1.06E+01	1.48E+01	1.06E-01	-1.81E-02	MND	4.16E-05	1.25E-03	2.25E-02	-3.16E-02	-3.09E-01						

<sup>8)</sup> PER = Primary energy resources.





## **END OF LIFE – WASTE**


Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	С3	C4	D
Hazardous waste	kg	8.76E+00	1.86E+00	6.09E+01	7.15E+01	1.22E+00	1.10E-01	MND	7.00E-04	1.44E-02	1.48E+00	3.73E-03	-1.21E+00						
Non-hazardous waste	kg	1.91E+02	3.45E+01	1.48E+03	1.71E+03	2.25E+01	3.62E+01	MND	9.54E-03	2.66E-01	4.79E+01	4.25E+01	-7.19E+01						
Radioactive waste	kg	2.59E-03	2.38E-04	4.67E-02	4.95E-02	1.55E-04	6.89E-06	MND	6.90E-08	1.84E-06	2.01E-05	5.25E-07	-2.42E-03						

## **END OF LIFE – OUTPUT FLOWS**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						
Materials for recycling	kg	0.00E+00	0.00E+00	8.30E-01	8.30E-01	0.00E+00	6.00E+00	MND	0.00E+00	0.00E+00	7.28E+00	0.00E+00	0.00E+00						
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.97E+01	MND	0.00E+00	0.00E+00	1.96E+02	0.00E+00	0.00E+00						

## **ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Global Warming Pot.	kg CO₂e	2.83E+02	7.53E+01	7.59E+02	1.12E+03	4.92E+01	7.12E+00	MND	4.78E-02	5.81E-01	5.57E+01	9.79E-01	-1.90E+01						
Ozone depletion Pot.	kg CFC-11e	1.06E-04	8.92E-07	3.46E-06	1.10E-04	5.83E-07	1.02E-08	MND	5.83E-10	6.88E-09	5.17E-08	1.98E-09	-2.31E-07						
Acidification	kg SO₂e	1.09E+00	1.97E-01	2.88E+00	4.17E+00	1.29E-01	3.95E-03	MND	3.05E-04	1.52E-03	1.17E-02	5.05E-04	-9.30E-02						
Eutrophication	kg PO <sub>4</sub> ³e	5.66E-01	4.81E-02	3.97E+02	3.97E+02	3.14E-02	1.23E-03	MND	7.13E-05	3.70E-04	3.03E-03	3.30E-04	-1.09E-02						
POCP ("smog")	kg C <sub>2</sub> H <sub>4</sub> e	7.08E-02	1.76E-02	1.40E-01	2.29E-01	1.15E-02	3.92E-04	MND	2.29E-05	1.36E-04	9.41E-04	1.89E-04	-5.20E-03						
ADP-elements	kg Sbe	4.26E-03	2.06E-04	7.46E-04	5.21E-03	1.35E-04	2.64E-06	MND	1.68E-08	1.59E-06	1.28E-05	2.09E-07	-3.25E-05						
ADP-fossil	MJ	3.94E+03	1.08E+03	8.00E+03	1.30E+04	7.08E+02	1.04E+01	MND	6.24E-01	8.36E+00	2.79E+01	2.09E+00	-2.17E+02						






IEL BY

## **ENVIRONMENTAL IMPACTS – GWP-GHG - THE INTERNATIONAL EPD SYSTEM**

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
GWP-GHG <sup>9)</sup>	kg CO₂e	2.85E+02	7.58E+01	7.62E+02	1.12E+03	4.95E+01	6.85E+00	MND	4.81E-02	5.84E-01	5.52E+01	1.02E+00	-1.91E+01						

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product as defined by IPCC AR 5 (IPCC 2013). In addition, the characterisation factors for the flows - CH4 fossil, CH4 biogenic and Dinitrogen monoxide - were updated in line with the guidance of IES PCR 1.2.5 Annex 1. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO2 is set to zero.








# **SCALING TABLE FOR DIFFERENT TYPES OF Micro optical fibre cables:**

This EPD covers the following listed Micro optical fibre cables:

Sr no.	Micro optical fibre cables	Weight (Kg)	Total number of fibres	GWP-total, (kgCO2e)	GWP-fossil, (kgCO2e)
31 110.	Wilcio Optical libre cables	Weight (Ng)	Total Hulliber of libres	GWF-total, (kgCOZE)	GVVF-105511, (NgCOZE)
1	144F Micro optical fibre cable 200μm	31.2	144	884.37	882.36
2	192F Micro optical fibre cable 200μm	48	192	1,236.36	1,233.66
3	240F Micro optical fibre cable 200μm	56.3	240	1,399.94	1,396.60
4	288F Micro optical fibre cable 200μm	61.8	288	1,631.76	1,627.74
5	432F Micro optical fibre cable 200μm	70.7	432	2,302.25	2,295.70
6	576F Micro optical fibre cable 200μm	101.5	576	3,143.26	3,135





# **VERIFICATION STATEMENT**

### VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

### THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

**#SIGNATURE#** 

