

|              |                                                         |
|--------------|---------------------------------------------------------|
| Product name | Patch SPX 1xSC/APC-SC/APC 1m SM G657A Blue 2mm LSZH LOW |
| Product code | 5069184                                                 |
| GTIN         | 7332811095023                                           |
| ETIM-Class   | EC001263                                                |



## PRODUCT SPECIFICATIONS

Fiberoptic patch cord singlemode G657A with blue 2mm simplex cable and SC/APC-SC/APC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols

## Measurements

|        |        |
|--------|--------|
| Length | 180 mm |
| Height | 10 mm  |
| Width  | 210 mm |
| Weight | 17 g   |

## Technical Specifications - Connectors

|                                           |         |
|-------------------------------------------|---------|
| Max insertion loss per connector (APC)    | 0.3 dB  |
| Max Optical Return Loss for APC connector | -65 dB  |
| Radius of Curvature APC                   | 5-12 mm |
| Max Vertex Offset                         | 50 µm   |

## Technical Specifications - Patch Cords

|                                              |                               |
|----------------------------------------------|-------------------------------|
| Length                                       | 1 m                           |
| Fibre Type                                   | ITU-T G.657 A1                |
| Outer Sheath Material                        | LSZH (Low Smoke Zero Halogen) |
| Colour of Cable Sheath                       | Blue                          |
| Cable Diameter                               | 2 mm                          |
| Temperature ranges for Operation             | -40°C to +85°C                |
| Temperature ranges for transport and storage | -40°C to +85°C                |
| Max Install Tensile Force                    | 98 N                          |
| Halogen Free                                 | Yes                           |