

Product name	ODF 19" 1U 24xSCD sliding Black, D210mm
Product code	5057751
GTIN	7332811123832
ETIM-Class	EC001130



PRODUCT SPECIFICATIONS

The draw-out-type ODF (optical distribution frame) is designed for the placement of up to 48 optical SC connectors indoors. The design of the patch panel enables to install it into a 19" rack. The ODF is equipped with needle holder for optical splice trays and strain reliefs for the cable FRP. Prepared for cable mounting at the rear (PG bushings).

- Capacity: Up to 48 optical SC connectors (24 duplex SC adaptors)
- Needle holder for optical splice trays
- Possibility to fit it with PG bushings
- Installation into a 19" base
- Height: 1U
- Depth: 210 mm
- Material: Black metal
- Option: Microduct shelf for microtube 5 mm management (ordered separately)

Measurements

Length	490 mm
Height	50 mm
Width	222 mm
Weight	3,000 g

Technical Specifications - ODFs

Fibre Count	48
Adapter Plate	24xSC Duplex
Preterminated	No
Sliding Enclosure	Yes
Mounting Type	19" rack
Number of Rack Spaces	1U
Depth - ODF	210 mm
Colour	Black RAL 9005
Material	Powder Coated Steel Sheet
Environment	Indoor