

Product name	Fiber panel ODF 6xSCD/LCQ for DIN-rail incl. splice holder, GRAY
Product code	5055315
GTIN	
ETIM-Class	EC001130



## PRODUCT SPECIFICATIONS

Robust mini-ODF for DIN-rail mounting.

- Capacity: 24 fibre (6xLCQ)
- Cable OD: 2.5-8mm (M16)
- Ingress Protection: IP20 (EN 60529)
- Impact Protection: IK10 (EN 50102)
- Material: Painted steel
- Color: Light gray RAL 7035

## Measurements

Length	139 mm
Height	140 mm
Width	51 mm
Weight	591 g

## Technical Specifications - Termination/Distribution Boxes

Environment	Indoor
Number of Entry/cable ports	3
Cable/duct diameters	2.5-8mm (M16)
Splice trays included	1

Splice Holder Included	Yes
Mounting	DIN-rail
Lockable	No
IP Codes	IP20
Impact protection degree	IK10
Halogen Free	Yes
Fire Resistance	UL 94 V0
UV Proof	Yes

## Technical Specifications - ODFs

Fibre Count	24
Adapter Plate	6XSC Duplex
Preterminated	No
Mounting Type	DIN Rail
Grommets	M16
Depth - ODF	139 mm
Colour	Light Gray RAL 7035
Material	Powder Coated Steel Sheet
Included Blinds	6
Environment	Indoor