

| | |
|--------------|--|
| Product name | Fibrebox MDB-M 144F splice only 7 in-/output for grommets IP65 |
| Product code | 5061022 |
| GTIN | 7332811368967 |
| ETIM-Class | EC002067 |



PRODUCT SPECIFICATIONS

The Fiber Optic Box MDB M is a durable fiber optic box, designed with the highly flexible FibeRoad system inside. The box can be configured to address a wide range of fiber optic splice and/or connectivity applications for PON, GPON and 5G networks. The engineered design provides IP65 protection from water / dust ingress and IK10 impact resistance to keep your critical network connections safe inside. The MDB M provides the ideal splicing solution for multi dwelling unit fiber distribution points or outdoor pole mounted splice applications.

Measurements

| | |
|--------|---------|
| Length | 132 mm |
| Height | 427 mm |
| Width | 290 mm |
| Weight | 1,250 g |

Technical Specifications - Termination/Distribution Boxes

| | |
|-----------------------------|--|
| Environment | Indoor, Outdoor |
| Number of splices | 144 |
| Number of connectors | 0 |
| Number of Entry/cable ports | 7 |
| Cable/duct diameters | 5x1.8–13 mm,+2x10–14mm, or indoors: 7x1.8–13mm |
| Mid-span access | Yes |
| Splice trays included | 0 |
| Number of splice trays | 6 |

| | |
|--------------------------|---------------------|
| Max Fibre Count per tray | 24 |
| Dark fiber storage | Yes |
| Lockable | Yes |
| IP Codes | IP65 |
| Impact protection degree | ik10 |
| Colour | Light Gray RAL 7035 |
| Material | pc / asa |
| Halogen Free | Yes |
| Fire Resistance | v0 |
| UV Proof | Yes |