

<b>Product name</b>	Fiber Optic Closure Coyote 622 BT UO 504F IP68 4 ports
<b>Product code</b>	5061136
<b>GTIN</b>	7332811377068
<b>ETIM-Class</b>	EC002598



## PRODUCT SPECIFICATIONS

The Fiber Optic Closure COYOTE® DOME 622 BT UO is a fiber optic closure using both stacking system and classic BT fiber optic trays for accessible fiber management in large trays. The closure is extremely durable and adapted to permanent immersion in water (IP68). The closure have a unique grommets system for easy installation.

- Capacity of up to 504 splices
- Scalable through gradual adding of trays
- Support for hinged splice trays
- Support for adapter splice trays or panels
- PLC Splitter capability (small format)
- Support for ribbon fibers
- Support for midspan (loop-through) cable
- Unique grommets system for cables with diameters 2.4–31.8 mm
- Increased impact protection and water ingress resistance even when permanently immersed in water (IP68)
- Optional pole and wall bracket
- Suitable for all types of networks

## Measurements

<b>Length</b>	218 mm
<b>Height</b>	574 mm
<b>Width</b>	218 mm
<b>Weight</b>	5,100 g

## Technical Specifications - Termination/Distribution Boxes

<b>Environment</b>	Outdoor
<b>Number of splices</b>	504
<b>Number of Entry/cable ports</b>	4
<b>Cable/duct diameters</b>	2.4 - 31.8 mm
<b>Mid-span access</b>	Yes
<b>Splice trays included</b>	0
<b>Number of splice trays</b>	7
<b>Max Fibre Count per tray</b>	72
<b>IP Codes</b>	IP68
<b>Impact protection degree</b>	IK10
<b>Colour</b>	Black
<b>Material</b>	Polypropylene Fiberglass
<b>UV Proof</b>	Yes