

| | |
|---------------------|--|
| Product name | Patch SPX 1xSC/APC-LC/APC 2m SM G657A2 White 3mm LSZH CPR Cca |
| Product code | 124562 |
| GTIN | 7332811384851 |
| ETIM-Class | EC001263 |

M E L
B Y
E

PRODUCT SPECIFICATIONS

Fibreoptic simplex reinforced (rugged) patch cords, singlemode G657A2 with pre-terminated connectors. To be used for patching or customer premises connections in optical networks. White color to blend in into a home environment. All products are of the highest quality with full traceability and tested according to all relevant industry standards.

Measurements

| | |
|---------------|--------|
| Length | 210 mm |
| Height | 15 mm |
| Width | 180 mm |
| Weight | 34 g |

Technical Specifications - Connectors

| | |
|--|--------|
| Max insertion loss per connector (APC) | 0.3 dB |
| Max Optical Return Loss for APC connector | -65 dB |
| Radius of Curvature APC | 5-12 |
| Max Vertex Offset | 50 µm |

Technical Specifications - Patch Cords

| | |
|-------------------|----------------|
| Length | 2 m |
| Fibre Type | ITU-T G.657 A2 |

| | |
|---|-------------------------------|
| Outer Sheath Material | LSZH (Low Smoke Zero Halogen) |
| Colour of Cable Sheath | White |
| Cable Diameter | 3 mm |
| Temperature ranges for Operation | -40°C to +85°C |
| Temperature ranges for transport and storage | -40°C to +85°C |
| Halogen Free | Yes |