

|                     |  |
|---------------------|--|
| <b>Product name</b> | Patch SPX 1xSC/APC-LC/APC 15m SM G657A2 White 3mm LSZH CPR Cca |
| <b>Product code</b> | 124567   |
| <b>GTIN</b>         | 7332811384905  |
| <b>ETIM-Class</b>   | EC001263   |

M E L  
B Y  
E

## PRODUCT SPECIFICATIONS

Fibreoptic simplex reinforced (rugged) patch cords, singlemode G657A2 with pre-terminated connectors. To be used for patching or customer premises connections in optical networks. White color to blend in into a home environment. All products are of the highest quality with full traceability and tested according to all relevant industry standards.

## Measurements

|               |        |
|---------------|--------|
| <b>Length</b> | 260 mm |
| <b>Height</b> | 45 mm  |
| <b>Width</b>  | 210 mm |
| <b>Weight</b> | 216 g  |

## Technical Specifications - Connectors

|  |        |
|--|--------|
| <b>Max insertion loss per connector (APC)</b>    | 0.3 dB |
| <b>Max Optical Return Loss for APC connector</b> | -65 dB |
| <b>Radius of Curvature APC</b>                   | 5-12   |
| <b>Max Vertex Offset</b>                         | 50 µm  |

## Technical Specifications - Patch Cords

|                   |                |
|-------------------|----------------|
| <b>Length</b>     | 15 m           |
| <b>Fibre Type</b> | ITU-T G.657 A2 |

|   |                               |
|---|-------------------------------|
| <b>Outer Sheath Material</b>                        | LSZH (Low Smoke Zero Halogen) |
| <b>Colour of Cable Sheath</b>                       | White                         |
| <b>Cable Diameter</b>                               | 3 mm                          |
| <b>Temperature ranges for Operation</b>             | -40°C to +85°C                |
| <b>Temperature ranges for transport and storage</b> | -40°C to +85°C                |
| <b>Halogen Free</b>                                 | Yes                           |