

Product name	Patch SM SPX 1xSC/APC-SC/APC G657A2 White 4mm LSZH 3m
Product code	
GTIN	
ETIM-Class	EC001263



PRODUCT SPECIFICATIONS

Fiberoptic patch cord singlemode G657A2 with white 4mm simplex cable and SC/APC-SC/APC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols.

Measurements

Length	210 mm
Height	15 mm
Width	180 mm
Weight	48 g

Technical Specifications - Connectors

Max insertion loss per connector (APC)	0.3 dB
Max Optical Return Loss for APC connector	-65 dB
Radius of Curvature APC	5-12
Max Vertex Offset	50 µm

Technical Specifications - Patch Cords

Fibre Type	ITU-T G.657 A2
Outer Sheath Material	LSZH (Low Smoke Zero Halogen)
Colour of Cable Sheath	White
Cable Diameter	4 mm
Temperature ranges for Operation	-40°C to +85°C
Temperature ranges for transport and storage	-40°C to +85°C
Halogen Free	Yes