

Product name	Patch cord SM SPX 1xSCA-LCA G657A1 White 3mm LSZH B2ca ARMOURED 5m
Product code	125810
GTIN	7332811390166
ETIM-Class	EC001263



PRODUCT SPECIFICATIONS

Fibreoptic simplex patch cords, singlemode G657A1 with pre-terminated connectors. To be used for patching between active equipment and cross connection between network connectivity equipment in optical networks. All products are of the highest quality with full traceability and tested according to all relevant industry standards.

The Armoured cable features a flexible stainless steel tube providing high protection in harsh environments. Having higher crush resistance and rodent resistance compared to standard patch cords.

Measurements

Weight	80.6 g
--------	--------

Technical Specifications - Connectors

Max insertion loss per connector (APC)	0.3 dB
Max Optical Return Loss for APC connector	-60 dB
Radius of Curvature APC	5-12 mm
Max Vertex Offset	50 µm

Technical Specifications - Patch Cords

Length	5 m
Fibre Type	ITU-T G.657 A1

Outer Sheath Material	LSZH (Low Smoke Zero Halogen)
Colour of Cable Sheath	White
Armouring	Stainless steel tube
CPR Classification	B2ca
Cable Diameter	3 mm
Temperature ranges for Operation	-40°C to +85°C
Temperature ranges for transport and storage	-40°C to +85°C
Halogen Free	Yes
Rodent Protection	Yes