

|              |                                          |
|--------------|------------------------------------------|
| Product name | PLC Splitter 1×16 2mm G6567A 1.5m LC/APC |
| Product code | 5188622                                  |
| GTIN         | 7332811201967                            |
| ETIM-Class   | EC003870                                 |



PRODUCT SPECIFICATIONS

Planar Lightwave Circuit (PLC) fiber optical splitters feature low IL and PDL, high isolation that suit for 1260 -1650nm optical fibre signals splitting and distributing in PON and CATV networks. Provide uniform division of an optical signal from one input fibre to multiple outgoing fibres.

Optical specifications do not include connector loss.

Measurements

|        |       |
|--------|-------|
| Weight | 180 g |
|--------|-------|

Technical Specifications - Splitter

|                                 |                |
|---------------------------------|----------------|
| Splitter Type                   | PLC - 2.0mm    |
| Port Configuration              | 1×16           |
| Connector Type                  | LC/APC         |
| Wavelengths                     | 1260 - 1650 nm |
| Fibre Type                      | ITU-T G.657 A1 |
| Max Insertion Loss              | 13.6 dB        |
| Max Loss Uniformity             | 1 dB           |
| Max Polarisation Dependant Loss | 0.3 dB         |
| Max Directivity                 | 55 dB          |
| Max Return Loss                 | 55 dB          |

|                                              |               |
|----------------------------------------------|---------------|
| Temperature ranges for Operation             | -40°C - +85°C |
| Temperature ranges for transport and storage | -40°C - +85°C |