

| | |
|--------------|--|
| Product name | Pigtail SM LC/UPC 1.0m 12-Pack G652D Blue 900µm LSZH |
| Product code | 5068410 |
| GTIN | 7332811325960 |
| ETIM-Class | EC000748 |



PRODUCT SPECIFICATIONS

Fibreoptic pigtail, singlemode G652D 900µm with one pre-terminated connector. To be used for splicing on a fibreoptic cable. Halogen-free according to EN 60754-1/2 and flame retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63. ID marked with a unique serial number for full traceability to component-level. Each package comes with individual measurement protocols. With pre-mounted 45 mm heat shrink sleeves.

Measurements

| | |
|--------|------|
| Weight | 86 g |
|--------|------|

Technical Specifications - Connectors

| | |
|---|---------|
| Max insertion loss per connector (UPC) | 0.2 dB |
| Max Optical Return Loss for UPC connector | -55 dB |
| Radius of Curvature UPC | 7-25 mm |
| Max Vertex Offset | 50 µm |

Technical Specifications - Pigtails

| | |
|-------------------------------|---------------|
| Connector Type | LC/UPC |
| Fibre Type | ITU-T G.652 D |
| Number of pigtails in package | 12 |
| Length | 1 m |

| | |
|-----------------------------------|---------------|
| Buffer Type | Semi Tight |
| Buffer Colour | Blue |
| Fibre Colour Sequence | EIA/TIA-598A |
| Splice Protection Sleeve Included | Yes |
| Temperature ranges for Operation | -40°C - +85°C |