

Product name	ODF 19 1U 24xSCD blownfiber Comb for 48 5mm microducts
Product code	5057749
GTIN	7332811177118
ETIM-Class	EC001130



PRODUCT SPECIFICATIONS

The draw-out-type ABF ODF (optical distribution frame) is designed for the placement of up to 48 optical SC connectors or 96 LC connectors and 48 microtubes indoors. Divided into two sections, one section handles the microtubes and the other handles fibre and termination. The solution provides full access from the front for easy installation and future expansions.

- Design: For air blown fiber (APF) installation
- Capacity fibre: Up to 48 SC or 96 LC optical connectors (24 SCD or 48 LCQ adaptors)
- Capacity microtubes: Up to 48 microtubes 5 mm
- Needle holder for optical splice trays
- Installation into a 19" base
- Height: 1U
- Depth: 290 mm
- Material: Black metal
- Option: Tube clamp 24 microtubes 7 mm (ordered separately)

Measurements

Length	285 mm
Height	43,6 mm
Width	482,5 mm
Weight	4,915 g

Technical Specifications - ODFs

Fibre Count	48
Adapter Plate	24xsc duplex
Micro Duct Bracket	48x5mm
Sliding Enclosure	Yes
Mounting Type	19" rack
Number of Rack Spaces	1 U
Colour	Black RAL 9005
Material	Powder Coated Steel Sheet
Environment	Indoor