


Product name	ORM1 Optical Socket 2xSCS incl. 1xSCU adaptor, pigtail and patch 0.5m
Product code	5052123
GTIN	7332811313745
ETIM-Class	EC001409



PRODUCT SPECIFICATIONS

The Fiber Access Terminal Box ORM 1 is designed to terminate an optical network using 2 to 4 optical fibers at a customer terminal point. It is installed indoors on a wall.

- Capacity 4 optical connectors
- Connector holder SC simplex or LC duplex
- Maximum capacity is 4 optical splices, heat shrink, RECORD splice, Fiberlock
- Attractive design for indoor usage
- Installing on a surface or flush-mounting box
- Simple optical management
- Direct fiber termination by a connector
- Standard socket dimensions
- Input possibility of fiber with connector
- Use only for fibers G657a, b

Ingress Protection	IP30 / IP54 (under special conditions)
Impact Protection	IK07
Flammability Degree	HB
Material	ABS

Color	RAL 9003
Dimensions (H × W × D)	116 × 81 × 25 mm / extended cover
	81 × 81 × 25 mm / short cover
Weight	0.08 kg
Environment	indoor
Number of Splices	1–4
Number of Connectors	1–4
Connector Type	SC/UPC

Measurements

Length	30 mm
Height	230 mm
Width	244 mm
Weight	98 g

Technical Specifications - Termination/Distribution Boxes

Environment	Indoor
Number of splices	4
Number of connectors	2
Connector Type	SC/UPC
Cable/duct diameters	max 6mm
Splice Holder Included	Yes
IP Codes	ip30
Impact protection degree	ik07
Colour	White RAL 9003
Material	ABS
Fire Resistance	hb
Weight	80 g