

| | |
|--------------|--|
| Product name | Straight connector 14mm DB Direct buried |
| Product code | 5040564 |
| GTIN | 7332811127632 |
| ETIM-Class | EC001475 |



PRODUCT SPECIFICATIONS

A high-performance DB connector dedicated to direct buried systems for FTTx networks (micro duct systems) to guarantee easy use and long service time. Reliable technology of push-in connection. Minimum distance between two tubes when connected, eliminating the risk of blockage during blowing. Compact design and intuitive installation. Tried-and-tested connection technology to ensure tensile strength and resistance to network expansion. Transparent body for easy fault location during installation. Perfect sealing IP68 for full protection against particle ingress. UL94 flame resistance enables indoor installations. Safety clip as an option for preventing risk of accidental disconnection. Date coding to guarantee quality and traceability. 100% leak-tested in production.

Measurements

| | |
|--------|-------|
| Length | 54 mm |
| Height | 25 mm |
| Width | 25 mm |
| Weight | 23 g |

Technical Specifications - Duct Connectors

| | |
|-----------------|--------------------------|
| Type | Straight - Direct Buried |
| For Duct Size | 14mm |
| Max Pressure | 25 Bar |
| Colour | Transparent |
| Fire Resistance | UL94 |
| IP Codes | IP68 |

Temperature ranges for Operation

-20°C - +80°C