

<b>Product name</b>	Endstop 5mm DI Direct install, 15 bar
<b>Product code</b>	5042420
<b>GTIN</b>	7332811196775
<b>ETIM-Class</b>	EC002065



## PRODUCT SPECIFICATIONS

A high-performance DI endstop dedicated to direct install systems for FTTx networks (micro duct systems) to guarantee easy use and long service time. Reliable technology of push-in connection. Ultra-compact design and intuitive installation. Tried-and-tested connection technology to ensure capability for network expansion. Transparent body for easy fault location during installation. Perfect sealing IP68 for full protection against particle ingress. UL94 V-2 flame resistance for indoor installations. Safety clip as an option for preventing risk of accidental disconnection. Date coding to guarantee quality and traceability. 100% leak-tested in production.

## Measurements

<b>Length</b>	17 mm
<b>Height</b>	11 mm
<b>Width</b>	11 mm
<b>Weight</b>	1 g

## Technical Specifications - End Caps

<b>Type</b>	Direct Installed
<b>For Duct Size</b>	5mm
<b>Max Pressure</b>	15 Bar
<b>Colour</b>	Transparent
<b>Fire Resistance</b>	UL94 V-2
<b>IP Codes</b>	IP68

## Temperature ranges for Operation

-15°C - +45°C