

<b>Product name</b>	Straight connector 10mm DI Direct install, 15 bar
<b>Product code</b>	5042415
<b>GTIN</b>	7332811196720
<b>ETIM-Class</b>	EC001475



## PRODUCT SPECIFICATIONS

A high-performance DI connector dedicated to direct install systems for FTTx networks (micro duct systems) to guarantee easy use and long service time. Reliable technology of push-in connection. Minimum distance between two tubes when connected, eliminating the risk of blockage during blowing. Ultra-compact design and intuitive installation. Tried-and-tested connection technology to ensure capability for network expansion. Transparent body for easy fault location during installation. Perfect sealing IP68 for full protection against particle ingress. UL94 V-2 flame resistance for indoor installations. Safety clip as an option for preventing risk of accidental disconnection. Date coding to guarantee quality and traceability. 100% leak-tested in production.

## Measurements

<b>Length</b>	42 mm
<b>Height</b>	16 mm
<b>Width</b>	16 mm
<b>Weight</b>	6 g

## Technical Specifications - Duct Connectors

<b>Type</b>	Straight - Direct Installed
<b>For Duct Size</b>	10mm
<b>Max Pressure</b>	15 Bar
<b>Colour</b>	Transparent
<b>Fire Resistance</b>	UL94 V-2

IP Codes	IP68
Temperature ranges for Operation	-15°C - +45°C