

Product name	Gas Block Connector 5mm Passive, cable 1,0-2,5mm
Product code	5042439
GTIN	7332811199240
ETIM-Class	EC002065



PRODUCT SPECIFICATIONS

A high-performance end cap gas block connectors dedicated to direct install systems for FTTx networks (micro duct systems). Easy-to-use product, providing quick and efficient sealing of the end of the micro duct and thereby long-term protection of the installation. One connector allows for several fibre cable OD combinations. Optic fibre cable visible as it passes through seal, allowing for considerable timesaving. Gas and watertight up to 1 bar. UL94 V-2 flame resistance for indoor installations. 100% push-in technology with optic fibre cable sealing. Safety clip as an option for preventing risk of accidental disconnection. Date coding to guarantee quality and traceability. 100% leak-tested in production.

Measurements

Length	10.5 mm
Height	17 mm
Width	17 mm
Weight	1 g

Technical Specifications - Glas Blocks

Type	Gas Block Seals
For Duct Size	5mm
Divisible	No
For Cable Diameter	1.0 - 2.5 mm
Gas and Water Tight Sealing	Yes
Sealing Level	1 Bar

Temperature ranges for Operation	-15°C - +45°C
Colour	Transparent
Fire Resistance	UL94 V-2
IP Codes	IP68