

Product name	Dual wavelength LS MM 850/1300nm (SC)
Product code	16305004
GTIN	7332811232848
ETIM-Class	EC000305



PRODUCT SPECIFICATIONS

SLS-21 adopts the latest technology to display the output power value and wavelength of the laser source directly in the LCD.

- Applicable on singlemode/multimode fibers
- Unique Output Power Display
- CW/MOD tones output
- Quick response, no warm-up
- Interchangeable connectors: FC/SC/ST
- 9V alkaline battery/AC adapter
- Power saving: Auto-off setting
- Pocketsize, lightweight and damp-dust-shock proof
- CE, FCC, FDA certificates

Measurements

Weight	30 g
--------	------

Technical Specifications - Test & Measurement Equipment

Fibre Type	Multimode
Calibrated Wavelengths	850nm, 1300nm
Power Range	≥-7
MOD Identification	
Connector Type	SC/UPC
Output Connector	SC
Battery Tye	9V Alkaline Battery
Battery Life	20 h
Power Save Feature	Yes
Light Source	850nm, 1300nm
Laser Type	FP, LD

Physical Specifications - Test & Measurement Equipment

Weight	300 g
Length	145 mm
Width	75 mm
Height	25 mm
Relative Humidity	95 %
Temperature ranges for Operation	-20°C to 50°C
Temperature ranges for transport and storage	-40°C to 70°C