

Product name	Emergency light SolidLed Slim Heated with self-test and LiFePO4 bat.
Product code	7346482
Product type	SLD612ST-LF-CD
GTIN	7332811361975
ETIM-Class	EC001957



PRODUCT SPECIFICATIONS

Solidled Slim Heated is equipped with Self-Test and LiFoPO4 battery The luminaire is also equipped with a smart multichannel charging (HCM). The control module keeps the internal temperature in the luminaire around 25°C. The battery can be discharged in cold conditions but will not start charging the battery until the internal temperature has reached 5°C using the heating element. This means that the luminaire will work safely for many years.

- for temperatures down to -20°C
- Autotest
- Pictograms for all directions included
- LongLife Batteries LiFePO4
- Adjustable plug for use as reference or emergency light fixture

Important to note!

After connecting mains voltage for the first time, the LED indicator will flash green at short intervals for 24h as the luminaire fast-charges the battery. After this, the luminaire will do a full battery test for 1h. After the test, the luminaire will again fast charge the battery for 24h. This means that the LED will blink for 49 hours after connection. Should the supply to the luminaire be interrupted during these hours, the luminaire will restart the process again.

Measurements

Length	71 mm
Height	130 mm
Width	280 mm
Weight	850 g

Technical specifications - Emergency Lights

Self Test	Yes
Mode	Exit sign
Mounting	Wall
Reading Distance	23 m
Dimensions (LxWxH)	71x280x130 mm
Number of Pictograms	4
Operating Voltage	230V AC
IP Classification	IP65
Battery Backup	1h
Operating Temperature	-20 - 40 °C
Battery	LiFePO4
Light Source	LED
Lumen	252
Power Consumption	0,05 A
Material	polykarbonat
RoHs	Yes